

Triumph®

PAPER CUTTERS

➔ 4810 D SEMI-AUTOMATIC CUTTER WITH DIGITAL DISPLAY

"SCS" (Safety Cutting System) package: transparent, electronically controlled front safety guard; transparent safety cover on rear table; main switch and safety lock with key; electronically controlled, true two-hand operation; 24 volt controls (low voltage); patented IDEAL safety drive; automatic blade return from every position; disc brake for instant blade stop; blade and cutting stick can be changed without removing covers; blade changing device covers cutting edge of blade; blade depth adjustment from outside of machine | electric blade drive | Solingen steel blade | solid steel blade carrier and adjustable blade guides | manual spindle clamp is guided on both sides to apply even pressure along entire cutting width | dual side guides on front and rear tables | spindle-guided back gauge with calibrated crank, narrow separations, and plastic gliders | digital display for precise back gauge positioning | bright, LED optical cutting line | all-metal construction | stand with storage shelf

Dimensions (D x W x H): 38 1/4 x 29 3/4 x 53 1/2 inches, Shipping weight: 531 lbs.




DIGITAL DISPLAY



The precise digital measurement readout for the back gauge can be displayed in cm or inches.

OPTICAL CUTTING LINE



An optical cutting line indicates exact location of cut and helps to perfectly position trim marks.

DUAL SIDE GUIDES



Two side guides combined with the precision back gauge allow exact positioning of even the smallest stock sizes.

➔ TRIUMPH 4810 D

Cutting width	18 7/8"
Cutting height	3"
Narrow cut	1 1/4"
Cutting length behind blade	17 11/16"
Table length in front of blade	13 3/8"
Motor	1.5 hp
Power supply	115 V, 60 Hz

Dealer:

MBM
CORPORATION

3134 Industry Drive
North Charleston, South Carolina 29418
800-223-2508, fax: 843-552-2974
www.mbmcorp.com

IDEAL.MBM
CORPORATION

1675 Sismet Road, unit 4
Mississauga, Ontario L4W 4K8
800-387-2528, fax: 905-840-1114
www.ideal-mbm.com