

Triumph®

PAPER CUTTERS

➔ 5551-06 EP PROGRAMMABLE HYDRAULIC CUTTER

"SCS" (Safety Cutting System) package: front safety light beams; safety cover on rear table; main switch and safety lock with key; electronically controlled, true two-hand operation; 24 volt controls (low voltage); patented IDEAL safety drive; automatic blade return from every position; automatic clamp return from every position; blade and cutting stick can be changed without removing covers; blade changing device covers cutting edge of blade; blade depth adjustment from outside of machine | high storage capacity programmable "EP" back gauge control module with 10 button keypad and LED display stores 99 programs, up to 99 steps each (up to 9 repeat cuts can be integrated into a program in a single step) | digital measurement readout in cm or inches (accurate to 1/10 mm or 1/100 inch) | module features memory key for repeat cuts (manual) and programmable eject function | program runs automatically in the program and memory mode | "set" function key for reference measurement | two programmable keys for quick setting of frequently used measurements | self-diagnostic system with error indication on display | hydraulic blade and adjustable hydraulic clamp drive | Solingen steel blade | solid steel blade carrier and adjustable blade guides | clamp is guided on both sides to apply even pressure along entire cutting width and is fully adjustable between 1,900 and 3,800 psi | false clamp and foot pedal for pre-clamping | electric, spindle-guided back gauge drive | electronic hand wheel with variable speed control for manual back gauge setting | bright, LED optical cutting line | mounted on casters | durable stainless steel work surface, front and rear | all-metal construction | optional side tables (shown) extend working surface

Dimensions (D x W x H): 55 x 42 x 54 inches (64 W with side tables), Shipping weight: 970 lbs. (1,007 with side tables).



5551-06 EP shown with optional side tables.



"EP" CONTROL MODULE



The "EP" back gauge control module stores 99 programs and frequently used measurements.

SAFETY LIGHT BEAMS



Safety light beams protect the operator and allow back gauge to automatically advance to the next cut.

➔ TRIUMPH 5551-06 EP

Cutting width	21 5/8"
Cutting height	3 5/8"
Narrow cut	1 1/4"*
Cutting length behind blade	22 7/16"
Table length in front of blade	18"
Motor	2 hp
Power supply	115 V, 60 Hz**

* 2 3/8" with false clamp

** 20 amp dedicated line required

Dealer:

MBM
CORPORATION

3134 Industry Drive
North Charleston, South Carolina 29418
800-223-2508, fax: 843-552-2974
www.mbmcorp.com

IDEAL.MBM
CORPORATION

1675 Sismet Road, unit 4
Mississauga, Ontario L4W 4K8
800-387-2528, fax: 905-840-1114
www.ideal-mbm.com