

# Triumph®

PAPER CUTTERS

## ➔ 6550 EP AUTOMATIC PROGRAMMABLE CUTTER

"SCS" (Safety Cutting System) package: transparent, electronically controlled front safety guard; transparent safety cover on rear table; main switch and safety lock with key; electronically controlled, true two-hand operation; 24 volt controls (low voltage); patented IDEAL safety drive; automatic blade return from every position; automatic clamp return from every position; disc brake for instant blade stop; blade and cutting stick can be changed without removing covers; blade changing device covers cutting edge of blade; blade depth adjustment from outside of machine | 25 1/2 inch cutting width accommodates parent stock | high storage capacity, programmable "EP" back gauge control module with 10 button keypad and LED display stores 99 programs (up to 99 steps each) and frequently used measurements | up to 9 repeat cuts can be integrated into a program in a single step | digital measurement readout in cm or inches (accurate to 1/10 mm or 1/100 inch) | control module features repeat cut and eject functions | "set" function key for reference measurement | self-diagnostic system with error indication on display | electric blade, clamp, and back gauge drive | Solingen steel blade | solid steel blade carrier and adjustable blade guides | automatic clamp is guided on both sides to apply even pressure along entire cutting width (can be lowered or raised independently from blade) | dual side guides on front and rear tables | spindle-guided back gauge with narrow separations and plastic gliders | electronic hand wheel with variable speed control for manual back gauge setting | bright, LED optical cutting line | all-metal construction | stand with storage shelf

Dimensions (D x W x H): 49 3/4 x 39 1/4 x 48 1/4 inches, Shipping weight: 801 lbs.




### "EP" CONTROL MODULE



The "EP" back gauge control module stores 99 programs and frequently used measurements.

### OPTICAL CUTTING LINE



An optical cutting line indicates exact location of cut and helps to perfectly position trim marks.

### AUTOMATIC CLAMP CONTROL



The automatic clamp control allows clamp to be moved up or down, independent of blade.

### ➔ TRIUMPH 6550 EP

|                                |               |
|--------------------------------|---------------|
| Cutting width                  | 25 1/2"       |
| Cutting height                 | 3"            |
| Narrow cut                     | 7/8"          |
| Cutting length behind blade    | 24"           |
| Table length in front of blade | 16 1/4"       |
| Motor                          | 2 hp          |
| Power supply                   | 115 V, 60 Hz* |

\* 20 amp dedicated line required

Dealer:

**MBM**  
CORPORATION

3134 Industry Drive  
North Charleston, South Carolina 29418  
800-223-2508, fax: 843-552-2974  
www.mbmcorp.com

**IDEAL.MBM**  
CORPORATION

1675 Sismet Road, unit 4  
Mississauga, Ontario L4W 4K8  
800-387-2528, fax: 905-840-1114  
www.ideal-mbm.com